

Connecting rod big end diameter Unit: mm (in)		Mark	Hole diameter													
			A	B	C	D	E	F	G	H	J	K	L	M	N	
Crankshaft pin journal diameter Unit: mm (in)	Axle diameter	Mark	59.000-59.001 (2.3228-2.3229)	59.001-59.002 (2.3229-2.3229)	59.002-59.003 (2.3229-2.3229)	59.003-59.004 (2.3229-2.3230)	59.004-59.005 (2.3230-2.3230)	59.005-59.006 (2.3230-2.3231)	59.006-59.007 (2.3231-2.3231)	59.007-59.008 (2.3231-2.3231)	59.008-59.009 (2.3231-2.3232)	59.009-59.010 (2.3232-2.3232)	59.010-59.011 (2.3232-2.3233)	59.011-59.012 (2.3233-2.3233)	59.012-59.013 (2.3233-2.3223)	
			A	55.961-55.960 (2.2032-2.2031)	0	0	0	0	0	01	01	01	1	1	1	12
B	55.960-55.959 (2.2031-2.2031)	0	0	0	0	0	01	01	01	1	1	1	1	12	12	
C	55.959-55.958 (2.2031-2.2031)	0	0	0	0	01	01	01	1	1	1	12	12	12	2	
D	55.958-55.957 (2.2031-2.2030)	0	0	01	01	01	1	1	1	1	12	12	12	2	2	
E	55.957-55.956 (2.2030-2.2030)	0	01	01	01	01	1	1	1	1	12	12	12	2	2	
F	55.956-55.955 (2.2030-2.2029)	01	01	01	01	1	1	1	1	12	12	12	2	2	2	
G	55.955-55.954 (2.2029-2.2029)	01	01	1	1	1	1	12	12	12	2	2	2	2	23	
H	55.954-55.953 (2.2029-2.2029)	01	1	1	1	1	12	12	12	2	2	2	2	23	23	
J	55.953-55.952 (2.2029-2.2028)	1	1	1	1	12	12	12	2	2	2	2	23	23	23	
K	55.952-55.951 (2.2028-2.2028)	1	1	1	12	12	12	2	2	2	2	23	23	23	3	
L	55.951-55.950 (2.2028-2.2028)	1	12	12	12	2	2	2	2	2	23	23	23	3	3	
M	55.950-55.949 (2.2028-2.2027)	12	12	12	2	2	2	2	23	23	23	3	3	3	34	
N	55.949-55.948 (2.2027-2.2027)	12	12	2	2	2	2	23	23	23	3	3	3	3	34	
P	55.948-55.947 (2.2027-2.2026)	12	2	2	2	2	23	23	23	3	3	3	3	34	34	
R	55.947-55.946 (2.2026-2.2026)	2	2	2	2	23	23	23	3	3	3	3	34	34	34	
S	55.946-55.945 (2.2026-2.2026)	2	2	23	23	23	23	3	3	3	3	34	34	34	4	
T	55.945-55.944 (2.2026-2.2025)	2	23	23	23	23	3	3	3	3	34	34	34	4	4	
U	55.944-55.943 (2.2025-2.2025)	23	23	23	23	3	3	3	3	34	34	34	4	4	4	